




BUSSOLE CONICHE TAPER BUSHES



esecuzione A
n° 3 fori



esecuzione B
n° 5 fori



Riferimento N.	Esecuzione	L	D ₁	Fori D ₂ ^{E₈} (con cava per chiavetta secondo DIN 6885/1)	Viti B.S.W.	Coppia di serraggio in N/m
1008	A	22	35	10-12-14-16-18-19-20-22-24-25	1/4"x1/2"	5,6
1108	A	22	38	14-19-20-24-25-28	1/4"x1/2"	5,6
1210	A	25	47,5	14-16-18-19-20-24-25-28-30-32	3/8"x5/8"	19,6
1215	A	38	47,5	14-19-20-24-25-28	3/8"x5/8"	19,6
1610	A	25	57	14-16-19-20-24-25-28-30-32-35-38-40-42	3/8"x5/8"	19,6
1615	A	38	57	19-20-22-24-25-28-30-32-35-38-40	3/8"x5/8"	19,6
2012	A	32	70	19-20-24-25-28-30-32-35-38-40-42-45-48-50	7/16"x7/8"	30,4
2517	A	45	85,5	19-20-24-25-28-30-32-35-38-40-42-45-48-50-55-60-65	1/2"x1"	48
3020	A	51	108	28-30-32-35-38-40-42-45-48-50-55-60-65-70-75	5/8"x1"1/4	90
3030	A	76	108	38-42-45-48-50-55-60	5/8"x1"1/2	90
3525	B	65	127	38-40-42-45-48-50-55-60-65-70-75-80	1/2"x1"1/2	113
3535	B	89	127	40-42-45-48-50-55-60-65-70-75-80-85-90	1/2"x1"1/2	113
4030	B	76	146	40-42-45-48-50-55-60-65-70-75-80-90	5/8"x1"1/2	169
4040	B	102	146	50-55-60-65-70-75-80-85-90-95	5/8"x1"3/4	169
4535	B	89	162	65-70-75-80-85-90-95-100-110-120-125	3/4"x2"	192
4545	B	115	162	65-70-75-80-85-90-95-100-110	3/4"x2"	192
5040	B	102	177,6	70-75-80-85-90-100-110-120-125	7/8"x2"1/4	272
5050	B	127	177,6	70-75-80-85-90-95-100-110-115-120-125	7/8"x2"1/4	272

Tutte le bussole coniche sono numerate usando un sistema internazionale che identifica velocemente diametro massimo del foro e la lunghezza del mozzo.